



# Inboard Racing Commission

## HYDROPLANE

SAFETY INSPECTION Revised – January, 2020

Boat Number \_\_\_\_\_ Class \_\_\_\_\_ Boat Name \_\_\_\_\_

Driver Helmet: Type \_\_\_\_\_ Snell # \_\_\_\_\_ Color \_\_\_\_\_

Life Jacket: Category B C ( ) Flotation Vest ( ) Sewn in Uniform

Sling: Rating in Pounds/Leg \_\_\_\_\_ # Of Legs \_\_\_\_\_ RE Certification Date (Every 5 Years) \_\_\_\_\_

Driver Restraint Belts: Material: ( ) Nylon ( ) Poly Width \_\_\_\_\_ Release: ( ) Lever ( ) Rotary

Condition: \_\_\_\_\_

Flotation required: Type \_\_\_\_\_ Location \_\_\_\_\_

Reinforced Cockpit Certification # \_\_\_\_\_ (must be permanently in boat) (Yes) (No)

Audio communication (radio, etc.) from shore to driver is mandatory. (Yes) (NO)

Air System: (YES) (NO) Comments \_\_\_\_\_

### Hull

- ( ) Steering – Cables & Puleys ( ) Rudder and Bracket
- ( ) Skid Fin and Mounting ( ) Strut
- ( ) Sling Attachment Lift Points – Accessible for viewing
- ( ) Motor Mounts ( ) Battery Mounts ( ) Propshaft Collars (2 screw or Split)
- ( ) Fuel tank mounting - where \_\_\_\_\_
- ( ) Fuel Lines ( ) Throttle Return Spring
- ( ) Mirrors ( ) Cockpit Padding

### Reinforced Cockpits

- ( ) Minimum 2” Clearance Above Driver to Cockpit or Canopy
- ( ) The Top of the Front of the Cockpit will be a Max. of 4” Below Eye Level
- ( ) Minimum ½” (9 lb) Ethofoam Support Behind Head(s)
- ( ) No Sharp Edges or Protrusions in Cockpit
- ( ) Energy Absorbing Foam Padding inside Cockpit
- ( ) Cockpit Area Sealed (Firewall)
- ( ) Rollover Lift Bracket on both Sponsons (3/4” Min. Hole)
- ( ) Critical Information on Bottom (3” Letters) ( ) Boat Number ( ) Rotary ( ) Air ( ) Head Restraint
- ( ) Canopies Positive Air Flow
- ( ) Canopies Internal and External Release ( ) Hand Hold Opening
- ( ) Escape Hatch (Yes) (No)
- ( ) Fire Resistant Driver’s Suit (Restraint Boats Only)

### Trailer

- ( ) Trailer Numbers
- ( ) Fire Extinguisher (minimum 3A30BC rating) Date (5 year max) \_\_\_\_\_

Inspector \_\_\_\_\_ Boat Rep \_\_\_\_\_

Event \_\_\_\_\_ Date \_\_\_\_\_