

Inboard Racing Commission SAFETY INSPECTION revised 5/12

To Be Completed by Contestant:	
Boat Number Class	Boat Name
Driver Helmet: Type Snell #	Color ()Restraint-flatbottom
Rider Helmet: Type Snell #	Color ()Restraint-flatbottom
Life Jacket: Category A A-100 B	() Flotation Vest ()Sewn in Uniform
Life Jacket: Category A A-100 B C Sling: Rating in Pounds/Leg # Of Legs	C () Flotation Vest ()Sewn in Uniform
Sling: Rating in Pounds/Leg # Of Legs	Pull Test Date (3 Yr. Max)
Driver Restraint Belts: Material () Nylon () Poly W	idth Release ()Lever () Rotary
Floatation required: Type Location _	
Reinforced Cockpit Certification#	(must be permanently in boat) (Yes) (No)
To Be Completed By Inspector:	
Hull:	
() Steering	
() Rudder and Bracket	
() Skid Fin and Mounting	
() Strut	
() Sling Attachment Lift Points – Accessible for v	viewing
() Motor Mounts	
() Battery Mounts	
() Propshaft Collars (2 screw or Split)	
() Fuel tank	
() Fuel Lines	
() Throttle Return Spring	
() Driveshaft Cover - Flatbottom	
() Whirlaway Functional - Flatbottom	
() Kill Switch Hooked to Jacket (Non Capsule only	y) Date Tested
() Mirrors	
() Cockpit Padding	
Safety Cage/Reinforced Cockpits	
() Minimum 2" Clearance Above Driver/Riding Mechanic to Cockpit or Canopy	
() The Top of the Front of the Cockpit will be a Max. of 4" Below Eye Level	
() Minimum ½" (9 lb) Ethofoam Support Behind Head(s)	
() No Sharp Edges or Protrusions in Cockpit	
1 0	
() Energy Absorbing Foam Padding inside Cockpit	
() Cockpit Area Sealed (Firewall)	
() Rollover Lift Bracket on both Sponsons (3/4" Min. Hole)	
() Critical Information on Bottom (3" Letters) ()Boat Number ()Rotary ()Air ()Head Restraint	
() Canopies Positive Air Flow	
() Internal and External Release/	
() Hand Hold Opening	. 1
() Escape Hatch Driver Exit To	ested
() Fire Proof Driver's Suit (Restraint Boats Only)	
() Trailer Numbers	
() Fire Extinguisher (minimum 3A30BC rating)	Date (5 year max)
Inspector	Event
Boat Rep	_ Date